



CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION



CERTIFICATE No.: 2019200907000056

NAME AND ADDRESS OF THE APPLICANT

Mibbo (Xia men) Automation Technology Co., Ltd
E802A,Taiwan Technology Business Incubator,Torch (Xiang' an) Industrial
Park,Xiamen,Fujian

NAME AND ADDRESS OF THE MANUFACTURER

Mibbo (Xia men) Automation Technology Co., Ltd
E802A,Taiwan Technology Business Incubator,Torch (Xiang' an) Industrial
Park,Xiamen,Fujian

NAME AND ADDRESS OF THE FACTORY

Mibbo (Xia men) Automation Technology Co., Ltd
6th Floor, 313-315 Xiangtian Road, Xiang 'an District, Xiamen City, Fujian Province,
China

NAME, MODULE AND SPECIFICATION

Switching Power Supply
See Appendix (Applies only to the altitude of 2000
meters and below; Applies only to the non tropical climate conditions)

THE STANDARDS AND TECHNICAL REQUIREMENTS FOR THE PRODUCTS

GB/T9254.1-2021 (Class A); GB 4943.1-2022; GB 17625.1-2022 (Class A)

This is to certify that the above mentioned products have met the requirements of
implementation rules for compulsory certification(REF NO. CNCA-C09-01: 2023)


Data of issue: 2023.10.17 Data of expiry: 2024.04.10

Validity of this certificate is subject to positive result of the regular follow up inspection by
issuing certification body until the expiry date.

Date of original certification: 2019.04.15

The certificate can be verified through CNCA's website :www.cnca.gov.cn or CEPREI's TEL:+86-20-87236606

Accredited by China National Accreditation Service for Conformity Assessment CNAS C0121P



CEPREI

General Manager:

CEPREI CERTIFICATION BODY

No. 76 West of Zhucun Avenue, Zhucun, Zengcheng District, Guangzhou, China
<http://www.ceprei.org>





CERTIFICATE FOR CHINA COMPULSORY PRODUCT CERTIFICATION

Appendix:

Page 1 of 1


Registration Number: 2019200907000056

MODEL: MPS-150WXV1S/1SL/1P/1PL (X=3.3, 4.2, 05, 7.5, 09, 12, 13.8, 15, 19, 24, 27, 29, 36, 42, 48 denotes output voltage, "V" represents the voltage symbol, "1" represents an input voltage of 200-240VAC, "S" for terminal belt cover. "L" represents the switching power supply electrolytic capacitor can work at-40°C at low temperature, "P" represents the switching power supply pin terminal block, "PL" represents the low temperature pin socket of switching power supply.

Input: 200-240VAC, 50/60Hz, 2A)

No	Model	The output voltage	Output current	Output power
1	MPS -150W3.3V1S, MPS -150W3.3V1SL MPS -150W3.3V1P, MPS -150W3.3V1PL	3.3VDC	19A	62.7W
2	MPS -150W4.2V1S, MPS -150W4.2V1SL MPS -150W4.2V1P, MPS -150W4.2V1PL	4.2VDC	19A	79.8W
3	MPS -150W05V1S, MPS -150W05V1SL MPS -150W05V1P, MPS -150W05V1PL	5VDC	19A	95W
4	MPS -150W7.5V1S, MPS -150W7.5V1SL MPS -150W7.5V1P, MPS -150W7.5V1PL	7.5VDC	17.3A	129.75W
5	MPS -150W09V1S, MPS -150W09V1SL MPS -150W09V1P, MPS -150W09V1PL	9VDC	16.7A	150.3W
6	MPS -150W12V1S, MPS -150W12V1SL MPS -150W12V1P, MPS -150W12V1PL	12VDC	12.5A	150W
7	MPS -150W13.8V1S, MPS -150W13.8V1SL MPS -150W13.8V1P, MPS -150W13.8V1PL	13.8VDC	10.5A	145W
8	MPS -150W15V1S, MPS -150W15V1SL MPS -150W15V1P, MPS -150W15V1PL	15VDC	10A	150W
9	MPS -150W19V1S, MPS -150W19V1SL MPS -150W19V1P, MPS -150W19V1PL	19VDC	7.9A	150W
10	MPS -150W24V1S, MPS -150W24V1SL MPS -150W24V1P, MPS -150W24V1PL	24VDC	6.5A	156W
11	MPS- 150W27V1S, MPS- 150W27V1SL MPS- 150W27V1P, MPS- 150W27V1PL	27VDC	5.6A	151.2W
12	MPS- 150W29V1S, MPS- 150W29V1SL MPS- 150W29V1P, MPS- 150W29V1PL	29VDC	5.2A	150.8W
13	MPS- 150W36V1S, MPS- 150W36V1SL MPS- 150W36V1P, MPS- 150W36V1PL	36VDC	4.3A	154.8W
14	MPS- 150W42V1S, MPS- 150W42V1SL MPS- 150W42V1P, MPS- 150W42V1PL	42VDC	3.6 A	151.2W
15	MPS- 150W48V1S, MPS- 150W48V1SL MPS- 150W48V1P, MPS- 150W48V1PL	48VDC	3.3A	158.4W

Note: This appendix is effective when used in conjunction with the certificate.



CEPREI

General Manager:

CEPREI CERTIFICATION BODY

No. 76 West of Zhucun Avenue, Zhucun, Zengcheng District, Guangzhou, China

<http://www.ceprei.org>

